

# SG36KTL-M

String Inverter



#### Secured Yield

- Max. efficiency 98.5 %
- Max. DC/AC ratio up to 1.3
- Up to 3 MPP Trackers



#### Flexible

- Power line communication optional
- Only 48 kg for easy installation



#### Intelligent Design

- Integrated string current monitoring function
- Integrated DC fuses and DC/AC surge protection



#### Reliable

- TÜV, CE, G59/3, BDEW



© 2017 Sungrow Power Supply Co., Ltd. All rights reserved.  
Subject to change without Notice. Version#1.0

<b>Input (DC)</b>		<b>SG36KTL-M</b>
Max. PV input voltage	1100 V	
Startup voltage	200 V	
Nominal input voltage	585 V	
MPP voltage range	200 - 1000 V	
MPP voltage range for nominal power	500 - 850 V	
No. of MPPTs	3	
Max. number of PV strings per MPPT	3 / 3 / 2	
Max. PV input current	88 A (33 A / 33 A / 22 A)	
Max. current for input connector	12 A	
<b>Output (AC)</b>		
Nominal AC output power	36000 W	
Max AC output power (PF=1)	36000 W	
Max. AC output apparent power	36000 VA	
Max. AC output current	53.5 A	
Nominal AC voltage	3 / N / PE or 3 / PE, 230 / 400 V	
AC voltage range	310 - 480 V	
Nominal grid frequency	50 Hz / 60 Hz	
Grid frequency range	45 - 55 Hz / 55 - 65 Hz	
THD	< 3 % (at nominal power)	
DC current injection	< 0.5 % In	
Power factor	> 0.99 @ default value at nominal power, (adj. 0.8 leading - 0.8 lagging)	
<b>Protections &amp; Functions</b>		
Anti-islanding protection	Yes	
VRT	Yes	
DC reverse connection protection	Yes	
AC short circuit protection	Yes	
Leakage current protection	Yes	
DC switch	Yes	
DC fuse	Yes	
PV string current monitoring	Yes	
Overshoot protection	DC Type II DIN rail surge arrester (40 kA) / AC Type II	
<b>System Data</b>		
Max. efficiency	98.50 %	
Euro. efficiency	98.30 %	
Isolation method	Transformerless	
Ingress protection rating	IP65	
Night power consumption	< 2 W	
Operating ambient temperature range	-25 to 60 °C (> 50 °C derating)	
Allowable relative humidity range	0 - 100 %	
Cooling method	Smart forced air cooling	
Max. operating altitude	4000 m (> 3000 m derating)	
Display	Graphic LCD	
Communication	RS485 / PLC (optional)	
DC connection type	MC4 (Max. 6mm <sup>2</sup> )	
AC connection type	Screw clamp terminal (Max. 50mm <sup>2</sup> )	
<b>Mechanical Data</b>		
Dimensions (W*H*D)	525*740*240 mm	
Mounting method	Wall bracket	
Weight	48 kg	
<b>Efficiency Curve</b>		